




This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CH'D DIM WAS Ø2.11 IS Ø2.10 - 2.08, ADDED MAKE SURE FACTORY MARKINGS ARE REMOVED AND MADE IN USA.	4/29/2009	RJC	
2		ADDED CHAMFERS AND CH'D FROM A 1-9/16in. 1/2 in. DRIVE SOCKET TO A 40mm 3/4 in. DRIVE SOCKET PER HELI-PRODUCTS STOCK. ALSO CH'D UPPER O.D. TOLERANCE WAS Ø2.11 IS 2.2 TO ACCOMMODATE 40mm SOCKET PER DW.	9/29/2009	WP	
2A		CH'D T/N WAS RBEA93-3300-20 ISA RBE350A93-3300-20.	6/19/2013	BIM	RW
3	15-0147	CH'D BUYOUT INFO WAS SNAP-ON IS PROTO. CH'D OAL WAS (2.23) IS 2.40 MAX. CH'D DIM WAS Ø2.10 - 2.08 IS (Ø2.25). ADDED NOTE 1. CORRECTED ORIGINAL No. REF. WAS RBEA93-3302-02 IS RBEA93-3300-20.	6/24/2015	RJC	JAG



ORIGINAL No. REF.
DO NOT USE FOR REF. ONLY
RBEA93-3300-20 = 350A93-3300-2.

NOTE:
1. PART OF AGUSTA KIT RBEA62309.

DART AEROSPACE	
TITLE TAIL ROTOR HUB SOCKET	
DWG NO. RBE350A93-3300-20	REV 3
MAT'L STEEL	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005	HEAT TREAT
.XX ± .01	FINISH
.X ± .1	BLACK OXIDE
ANGLES ± 5°	SPEC
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	USED ON MODEL
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	AS350A
SCALE 1:2	DATE 3/19/2009
SHEET 1 OF 1	

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
				1	SOCKET	STEEL	40mm -6 POINT 3/4 in. DR. (PROTO #J07540M) MODIFIED	